



| code    | inside diameter |       | outside diameter |      | working pressure |     | burst pressure |      | weight nominal |        | length max |     |
|---------|-----------------|-------|------------------|------|------------------|-----|----------------|------|----------------|--------|------------|-----|
|         | mm              | inch  | mm               | inch | bar              | psi | bar            | psi  | kg/m           | lbs/ft | m          | ft  |
| 1019007 | 19              | 3/4   | 33               | 1,30 | 40               | 600 | 120            | 1800 | 0,74           | 0,50   | 120        | 400 |
| 1252674 | 25              | 1     | 39               | 1,54 | 40               | 600 | 120            | 1800 | 0,87           | 0,58   | 120        | 400 |
| 1291998 | 38              | 1-1/2 | 51,5             | 2,03 | 40               | 600 | 120            | 1800 | 1,21           | 0,81   | 120        | 400 |
| 1391534 | 51              | 2     | 60               | 2,36 | 40               | 600 | 120            | 1800 | 0,87           | 0,58   | 120        | 400 |



EN

## Artificial snow hose

**Application:** softwall hose for the delivery of water under pressure from both the main water system to the snow gun and to the gun itself.

**Temperature:** from -40°C (-40°F) to +60°C (+140°F).

**Construction**

**Tube:** black, smooth, synthetic rubber.

**Reinforcement:** high strength synthetic cord.

**Cover:** blue, smooth (wrapped finish), long lasting synthetic rubber, weathering and ozone resistant.

**Branding:** continuous yellow stripe "IVG Water (family logo)...".

**Also available upon request:** 1. Different diameters 2. Different working pressures.

RU

## Рукав для снежных пушек

**Применение:** напорный рукав для подачи воды в системах искусственного заснеживания - снегогенераторах, как вентиляторных, так и мачтовых.

**Температура:** от -40°C до +60°C.

**Конструкция**

**Внутренний слой:** черного цвета, гладкий, из синтетического каучука.

**Усиление:** высокопрочный синтетический корд.

**Покрытие:** голубого цвета, гладкое (отпечаток текстильного бандажа), из износостойкого синтетического каучука.

**Маркировка:** желтая маркировочная лента "IVG Water (логотип группы)...".

**В наличии по запросу:** 1. Другие диаметры 2. Другое рабочее давление.